


Electronic Sounder and Beacon

General

This electronic sounder is designed for use with fire alarm systems, security systems and industrial signaling systems. Combined sounder and beacon provides an audio-visual warning which is suitable for places where high sound output and visual indication is required.

Characteristics

- 32 signal tones selectable by Dip switch.
- High sound output with low current consumption.
- High efficiency lens for maximum light output.
- Volume Control as standard.
- Two sets of IN and OUT terminals, easy for installation.

Electronic Sounder and Beacon
 Model : AH-03127-S, AH-03127-BS
 Manufactured : HORING LIH INDUSTRIAL CO.,LTD.
 Approvals : 



AH-03127-BS



AH-03127-S

Specifications

Model	AH-03127-S	AH-03127-BS
Voltage	24V DC	
Current Consumption 24V DC (MAX)	35mA	40mA
Sound Output 24V DC dB (A) at 1 meter	Max. 114	
Volume Control	0 to -20dB adjustment	
Ingress Protection	IP44	
Ambient Temperature	-25°C ~ +80°C I	
Material	Fire-proof plastic	
Dimensions	92.5mm(Dia.) x 94mm(H)	92.5mm(Dia.) x 110mm(H)
Weight	254g	278g

Order information

AH-03127-S	Electronic Sounder
AH-03127-BS	Electronic Sounder and Beacon