

IEEE 802.3 AT, 8-port 10M/100M Desktop PoE Fast Ethernet Switch

CSH-8008P

FEATURES

- 8 PSE/Power over Ethernet Ports
- 11" Metal Case
- Rack-Mount to 19" Cabinet
- Auto-MDI/MDI-X
- Auto-Negotiation
- Non-Blocking
- Internal Power Supply



DESCRIPTION

CSH-8008P is IEEE 802.3 AT, 8-port 10M/100M Desktop PoE Fast Ethernet Switch that is designed for small or medium network environment to strengthen its network connection. This product is compact in size, making it ideal for Desktop users with limited space. It also gives you the option of installing it in a 19" cabinet by rack-mount kits or underneath a desk.

IEEE 802.3af Power over Ethernet (PoE) ports

CSH-8008P features 8 IEEE 802.3at Power over Ethernet (PoE) ports supplying up to 30 watts per port. This product can convert standard 90~260V/AC power into low-voltage DC that runs over existing LAN cable to power up IEEE 802.3af compliant network accessories. It also features PoE awareness to verify whether the network device receive power is IEEE 802.3at compliant, or only the data will be sent through LAN cable. By adding PS-588 to existing networking, installing networking products such as Access Points and IP cameras can be easily managed and set up. Wireless device deployments are easily located with available power outlets and network administrators don't need to use heavy AC power adapters anymore.

No Special Networking Cable Required

By adding PoE devices, you can use an existing standard Cat-5 Ethernet cable without a new electrical outlet for both power and data. It helps you reduce installation time and cost.

Auto-MDI/MDI-X

Every port can automatically sense your type of cable, so there is no need for crossover cables whether you are connecting this switch to another switch or to a computer.

Auto-Negotiation

Every port can automatically sense if the connected network devices are running at 10Mbps or 100Mbps and Half/Full-Duplex mode, and adjust accordingly.

Non-Blocking

This switch receives and forwards traffic seamlessly with its non-blocking wire-speed. Every port simultaneously supports up to 200Mbps of bandwidth in full-duplex mode. This feature provides full wire speed to the connected devices and allows you to run a smooth network.

Store and Forward

By this function, this switch can maximize network performance while minimizing the propagation of bad network packets.

SPECIFICATIONS

Standards	• IEEE-802.3at
	• IEEE 802.3 10BaseT
	• IEEE 802.3u 100BaseTX
	• IEEE 802.3x Flow Control
Features	• Number of Ports: 8 PSE/Power over Ethernet Ports
	• MAC Address: 4K
	• Buffer Memory: 1.625M bits
	• Transmission Method: Store and Forward
Filtering/Forwarding Rates	• 100Mbps port - 148,800pps
	• 10Mbps port - 14,880pps
Transmission Media	• 10BaseT Cat. 3, 4, 5 UTP/STP
	• 100BaseTX Cat. 5 UTP/STP
Led Indicators	• Per Port: Link/Act, PoE Act/Status
	• Per Unit: Power
Power Input	• 100~240V/AC, 50~60Hz
Power Output	• 48V/DC Per Port Output – 30 W Max Per Port
	• 8 Ports at Full 15.4 W Output Supported per port
Power Consumption	• 130 Watts (Max)
Dimensions	• 44 × 266 × 160 mm (Hx W × D)
Weight	• 1.4 kg
Operating Temperature	• 0 to 45°C
Storage Temperature	• -20 to 90°C
Humidity	• 10 to 90% RH (non-condensing)
Certifications	• FCC Class A, CE

