

# ZK-KR102E-MF

Access reader

Access with Mifare card or PIN

LED and acoustic indicator

Wiegand 26

Compatible with ZK-C3

Suitable for exterior IP65



ZKTeco

Access reader for controller

Access with Mifare card and/or password

LED indicator

Wiegand 26

Suitable for exterior IP65

Compatible with ZK-C3-200 controller

# Specifications

|                             |                                             |
|-----------------------------|---------------------------------------------|
| <b>Brand</b>                | ZKTeco                                      |
| <b>Model</b>                | KR102E                                      |
| <b>Reading distance</b>     | Up to 10cm                                  |
| <b>Read time</b>            | < 300ms                                     |
| <b>Identification modes</b> | 13,56 MHz Mifare card, PIN and combinations |
| <b>Outputs</b>              | Wiegand OUT 26bits   Pin 8bits              |
| <b>Compatibility</b>        | ZKTeco C3 controllers and ZKTeco INBIO      |
| <b>Power supply</b>         | DC 6~14 V / 70 mA max.                      |
| <b>Degree of protection</b> | Suitable for exterior IP65                  |
| <b>Temp. operation</b>      | -20° C ~ +65° C                             |
| <b>Dimensions</b>           | 86(W) x 86(H) x 16.5(Fo)mm                  |
| <b>Weight</b>               | 50 g                                        |